DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

A21EA
Revision No. 10
Canadair
CL-600-1A11(CL-600)
CL-600-2A12(CL-601)
CL-600-2B16(CL-601-3A) & (CL-601-3R)
& (CL-604)
CL-600-2B19 (Regional Jet Series 100)
July 30, 1999

TYPE CERTIFICATE DATA SHEET NO. A21EA

This data sheet which is part of Type Certificate No. A21EA, prescribes conditions and limitations under which the product for which the Type Certificate was issued meets the airworthiness requirements of the Federal Aviation Regulations.

Type Certificate Holder: Bombardier Inc.
P.O. Box 6087, Station Centre-Ville
Montreal, Quebec, Canada H3C 3G9

I - Model CL-600-1A11 (Transport Category), Approved November 7, 1980, by the FAA and August 10, 1980, by the Canadian Department of Transport (DOT).

Engines: Two AVCO Lycoming ALF-502L or ALF-502L-2

Fuel

Type	Specifications		
	Canada	U.S.A.	U.K.
Jet A	CAN2-3.23-M81	ASTM D1655	D. Eng RD2494
Jet A-1	CAN2-3.23-M81	ASTM D1655	D. Eng RD2494
Grade JP-5	-	MIL-T-5624	D. Eng RD2452
Grade JP-8	-	MIL-T-83133A	D. Eng RD2453
Jet B	CAN2-3.22-M80	ASTM D1655	D. Eng RD2486
JP-4	CAN2-3.22-M80	MIL-T-5624	D. Eng RD2486

Jet A and Jet A-1 fuels must contain an approved anti-icing additive unless Canadair Modification Summary 600-702 and Lycoming Service Bulletin ALF-502-79-0007 are incorporated.

Oil: Engine, APU, Generator Adapter:
MIL-L-7808 (Type I) or MIL-L-23699 (Type II) or other approved oils as identified in the Maintenance Manual (refer to Approved Publications).

Engine Limits

	SL Static Thrust(lb.)	Compressor RPM		Interturbine Temperature	
		LP %N1	HP %N2	°C	°F
Takeoff (5 minutes)	7500	96.0	98.2	904	1660
Maximum Continuous	7100	96.0	96.4	877	1610
*Starting maximum				823	1513

Maximum Oil Temperature: Normal 143°C(290°F)
**Transient 170°C(338°F)

*Time limit 10 seconds above 793°C(1460°F)

**Permitted during power reduction. Normal temperature must be achieved within two minutes of achieving steady state operation.

Page No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Rev. No.	10	7	6	7	10	7	7	7	10	7	7	7	10	7	7
Page No.	16	17	18	19	20	21	22	23	24	25					
Rev. No.	10	7	7	7	7	7	7	7	7	7					

Oil Pressure	Maximum	Sea Level	120 p.s.i.	
	Minimum	At steady state low or high idle	30 p.s.i.	

APU Limits	Maximum RPM	110%		
	Maximum EGT:		°C	°F
	Starting (10 Seconds)		974	1785
	Running		731	1348

Airspeed Limits (CAS) (See NOTE 1)	V_{mo} and M_{mo} (maximum operating)		m.p.h.	Knots	Mach
	Sea level to 10000 ft.		345	300	
	above 10000 ft.		368	320	0.79
	V_{fe} (Flaps extended)	20°	265	230	
		30°	226	196	
		45°	193	168	
	V_a (maneuvering) (See Flight Manual for variation of V_a with altitude and aircraft weight).				
	V_{1o}(Landing gear operation)		226	197	
	V_{le} (Landing gear extended)		288	250	

C.G. Range (See NOTE 1)

Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 31300	16% (+502.848)	- - -
36500	18% (+504.701)	28% (+513.965)
25800	- - -	33% (+518.598)
24000	- - -	33% (+518.598)

Straight line variation between points given.

Datum: Fuselage station 0, located 375 inches forward of weighing datum jig point.

Mean Aerodynamic Chord (MAC): 92.644 in. (Leading edge of MAC from datum at +488.025 in.)

Leveling Means: Target plate and plumb bob bracket within rear fuselage, at fuselage station 718.

Maximum Weights (See NOTE 1)

	lb.*
Ramp	36500
Takeoff	36000
Landing	30500
Zero Fuel	25800
Minimum flight weight	24000

*Certain aircraft are eligible for operation at an increased weight. See AFM as in approved publications.

Minimum Crew: Two (Pilot and Co-pilot)

Maximum Occupants (See NOTE 1): Twenty-one (includes crew).

Fuel Capacity

	U.S. Gal	Imp. Gal.	Kg.	Weight, lb.	Mom. Arm-in.
2 main tanks (each)	732.5	611.3	2259.1	4981	(+506.5)
1 center tank	751	625.8	2316.1	5107	(+457.5)
total	2216	1848.4	6834.3	15069	- - -
Usable					
2 main tanks (each)	725	605	2236	4930	(+506.5)
1 center tank	750	625	2313	5100	(+457.5)
total	2200	1835	6785	14960	- - -

See NOTE 1(b) for system fuel.

Oil Capacity

	U.S. Gal	Imp. Gal.	Kg.	Weight, lb.	Mom.Arm-in.
2-engines (each)	3.69	3.07	12.88	28.4	(+623)
total	7.38	6.14	25.76	56.8	(+623)
Usable					
2-engines (each)	1.94	1.61	6.76	14.9	(+623)
total	3.87	3.22	13.52	29.8	(+623)

See NOTE 1(c) for system oil.

APU					
usable	.408	.340	1.43	3.144	(+675)
total	.714	.594	2.49	5.5	(+675)
unusable	.306	.254	1.06	2.356	(+675)

Maximum Operating Altitude (See NOTE 1)
Take off and landing: 5000 ft.
En route: 40000 ft.
41000 ft. with Canadair Limited Modification Summaries 600-1923 and 600-8330 incorporated.

Control Surface Movements

Rudder	20° (+1.0°, - 0.5°)Left	20° (+1.0°, - 0.5°)Right
Elevator	23.6°(+ or - 1.0°)Up	18.4°(+ or - 1.0°)Down
Horizontal Stabilizer	0°(+0.5° or -0.25°)LE Up	-9°(+ or -0.5°)LE Down
Aileron	20.8°(+ or - 1.0 °)Up	21.3°(+ or - 1.0°) Down
Flap - Inboard		0° - 45° (+ or -1°) Down
- Outboard		0° -46.7°(+ or -1°) Down
Flight spoiler	0° -40°(+3°, -0°)Up	

Serial Numbers Eligible: 1002, 1004 and subsequent

Service Information: Service Bulletins, structural repair manuals, and aircraft flight manuals which contain a statement that the document is Transport Canada approved or Transport Canada approved through the Manufacturers Design Approval Representative are accepted by the FAA and are considered FAA approved. These approvals pertain to the type design only.

II - Model CL-600-2A12 (Transport Category), Approved March 11, 1983, by the FAA and February 25, 1983, by the Canadian Department of Transport (DOT).

Engines: Two General Electric CF-34-1A or *

Fuel

Type	Specifications		
	Canada	U.S.A	U.K.
Jet A	CAN2-3.23-M81	ASTM D1655	D. Eng RD2494
Jet A-1	CAN2-3.23-M81	ASTM D1655	D. Eng RD2494
Grade JP-5	-	MIL-T-5624	D. Eng RD2452
Grade JP-8	-	MIL-T-83133A	D. Eng RD2453
Jet B	CAN2-3.22-M80	ASTM D1655	D. Eng RD2486
JP-4	CAN2-3.22-M80	MIL-T-5624	D. Eng RD2486

Oil: Engine, APU, Generator Adapter:
MIL-L-7808 (Type I) or MIL-L-23699 (Type II) or other approved oils as identified in the Maintenance manual (refer to Approved Publications).

Engine Limits

	SL Static Thrust (lb.)	Compressor RPM		Interturbine Temp.**		
		LP %N1	HP %N2	°C	°F	Time Limit
Max. takeoff (APR operating)	9140	98.6	99.4	857	1576	5 minutes
Max. takeoff (APR not operating	8650	96.2	98.2	842	1548	5 minutes
Max. continuous	8920	98.6	99.2	838	1540	
Idle range			62.9-64.0			
Min.Idle in icing conditions			64.0			
Transient:						
Takeoff (APR operating)				886	1627	2 minutes
Takeoff (APR not operating)				864	1588	2 minutes
Start/relight				899	1650	25 seconds
				885	1625	50 seconds

* One - General Electric CF-34-3A and one CF-34-3A2 or
One - General Electric CF-34-1A and one CF-34-3A or
Two - General Electric CF-34-3A or
Two - General Electric CF-34-3A2
Service Bulletin 601-0238 "Engines use of 3A engines at 3A power settings," must be incorporated.

** See AFM as listed in Approved Publications for CF-34-3A and CF-34-3A2 engines ITT limits.

NOTE

1. Above 40000 feet, engine anti-ice bleed or air conditioning unit must be selected ON for each engine.

2. Engine Limits with APR Operating are only applicable to Outside Air Temperatures of -4 °F (-20°C) and above.

		°C	°F
Oil Temperature	Maximum Permissible (15 minutes Maximum):	+163	325
	Maximum for Single Engine Climb (60 minutes maximum)	+155	311
	Maximum continuous:	+150	302
	Minimum for starting:	- 40	- 40

Oil Pressure
Maximum Transient Cold Start: 100 psi (Six minutes maximum)
Maximum Continuous: 95 psi

Minimum at steady state idle: 25 psi
at takeoff (power): 40 psi

APU Limits

Maximum RPM 110%

Maximum EGT:	°C	°F
Starting (10 seconds)	974	1785
Running	731	1348

Airspeed Limits (CAS)

V_{mo} and M_{mo} (maximum operating)	m.p.h.	Knots	Mach
Sea level to 10000 ft.	345	300	-
10000 ft. to 21420 ft.	420	365	-
21420 ft. to 25740 ft.	-	-	0.79
25740 ft. to 28640 ft.	385	335	
above 28640 ft.	-	-	0.835

V_{fe} (Flaps extended)	20°	265	230
	30°	226	196
	45°	215	187

V_a (maneuvering)
(See Flight Manual for variation of V_a with altitude and aircraft weight).

V_{1o} (Landing gear operation)	226	196
V_{1e} (Landing gear extended)	288	250

C.G. Range (See NOTE 1)

Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
25000 to 42250	16 % (+502.848)	- - -
42250	- - -	30% (+515.818)
31000	- - -	35% (+520.450)
25000	- - -	35% (+520.450)

Straight line variation between points given.

Datum — Fuselage station 0, located 375 inches forward of weighing datum jig point.

Mean Aerodynamic Chord (MAC) — 92.644 in. (Leading edge of MAC from datum at +488.025 in.)

Leveling Means — Target plate and plumb bob bracket within rear fuselage, at fuselage station 718.

Maximum Weights (See NOTE 1)

	1b.*
Ramp	42250
Takeoff	42100
Landing	36000
Zero Fuel	29500
Minimum flight weight	25000

*Certain aircraft are eligible for operation at an increased weight. See AFM as in approved publications.

Minimum Crew — Two (Pilot and Co-pilot)

Maximum Occupants (See NOTE 1) — Twenty-two (includes crew).

Fuel Capacity		U.S. Gal	Imp. Gal	Kg.	Weight, lb.	Mom. Arm-in.
	2 main tanks (each)	721	600.4	2224	4903	(+506.6)
	Fuselage Tanks	1012	842.7	3121	6882	(+455.6)
	Total	2454	2043.4	7569	16688	
	Usable					
	2 main tanks (each)	720	600	2221	4896	(+506.6)
	Fuselage tanks	1011	842	3118	6875	(+455.6)
	Total	2451	2042	7560	16667	
	See NOTE 1(b) for system fuel.					
Oil Capacity		U.S. Gal	Imp. Gal.	Kg.	Weight, lb.	Mom. Arm-in.
	2-engines (each)	1.70	1.42	5.94	13.09	(+656.0)
	Total	3.40	2.83	11.88	26.18	(+656.0)
	Usable					
	2-engines (each)	1.38	1.14	4.80	10.59	(+656.0)
	Total	2.75	2.29	9.60	21.18	(+656.0)
	See NOTE 1(c) for system oil.					
	APU					
	usable	.408	.340	1.43	3.144	(+646.0)
	Total	.714	.594	2.49	5.5	(+646.0)
	unusable	.306	.254	1.06	2.356	(+646.0)
Maximum Operating Altitude	Take off and landing:	10000 ft.				
	En route:	41000 ft.				
Control Surface Movements	Rudder	25°(+1.0°, -.5°) Left			25°(+1.0°, -.5°) Right	
	Elevator	23.6°(+ or - 1.0°)Up			18.4°(+ or - 1.0°)Down	
	Horizontal Stabilizer	0°(+0.5° or -0.25°)LE Up			-9°(+ or - 0.5°)LE Down	
	Aileron	20.8°(+ or - 1.0°)Up			21.3°(+ or - 1.0°) Down	
	Flap - Inboard				0° -45°(+ or - 1°) Down	
	- Outboard				0° -46.7°(+ or -1°) Down	
	Flight spoiler	0° -40°(+3°, -0°) Up				
Serial Numbers Eligible	1003, 3001, and subsequent					

Service Information: Service Bulletins, structural repair manuals, and aircraft flight manuals which contain a statement that the document is Transport Canada approved or Transport Canada approved through the Manufacturers Design Approval Representative are accepted by the FAA and are considered FAA approved. These approvals pertain to the type design only.

III - Model CL-600-2B16 (Transport Category), Approved April 30, 1987, by the FAA and April 21, 1987, by the Canadian Department of Transport (DOT).

Engines	(variant CL-601-3A)	Two General Electric CF-34-3A or CF-34-3A2 or One General Electric CF-34-3A and one CF-34-3A2
	(variant CL-601-3R)	Two General Electric CF-34-3A1 (Serial Number 5135 and subsequent) Approved by the FAA 15 July 1995.
	(variant CL-604)	Two General Electric CF 34-3B (Serial Number 5301 and subsequent) Approved by the FAA 31 May 1995.

Fuel	Type	Specifications		
		Canada	U.S.A.	U.K.
	Jet A	CAN2-3.23-M81	ASTM D1655	D. Eng RD2494
	Jet A-1	CAN2-3.23-M81	ASTM D1655	D. Eng RD2494
	Grade JP-5	-	MIL-T-5624	D. Eng RD2452
	Grade JP-8	-	MIL-T-83133A	D. Eng RD2453
	Jet B	CAN2-3.22-M80	ASTM D1655	D. Eng. RD2486
	JP-4	CAN2-3.22-M80	MIL-T-5624	D. Eng RD2486

Oil

Engine, APU, Generator Adapter:

MIL-L-7808 (Type I) or MIL-L-23699 (Type II) or other approved oils as identified in the Maintenance manual (refer to Approved publications).

CL-601 3A & 3R Variants

Engine Limits	SL Static Thrust (lb.)	Compressor RPM		Interturbine Temp.**		
		LP %N1	HP %N2	°C	°F	Time Limit
Max. takeoff (APR operating)	9140	98.6	99.4	871	1600	5 minutes
Max. takeoff (APR not operating)	8650	96.2	98.2	860	1580	5 minutes
Max. continuous	8920	98.6	99.2	860	1580	
Idle range			62.9-64.0			
Min. Idle in icing conditions			64.0			
Transient:						
Takeoff (APR operating)				900	1652	2 minutes
Takeoff (APR not operating)				878	1612	2 minutes
Start/relight				899	1650	25 seconds
				885	1625	50 seconds

** See AFM as listed in Approved Publications for CF-34-3A and CF-34-3A2 engines ITT limits.

NOTE

1. Above 40000 feet, engine anti-ice bleed or air conditioning unit must be selected ON for each engine.

2. Engine Limits with APR Operating are only applicable to Outside Air Temperatures of -4°F (-20°C) and above.

		°C	°F
Oil Temperature	Maximum Permissible (15 minutes Maximum):	+163	325
	Maximum for Single Engine Climb (60 minutes maximum)	+155	311
	Maximum continuous:	+150	302
	Minimum for starting:	- 40	- 40
Oil Pressure	Maximum Transient Cold Start:	100 psi (Six minutes maximum)	
	Maximum Continuous:	95 psi	
	Minimum at steady state idle:	25 psi	
	at takeoff (power):	40 psi	
APU Limits	Maximum RPM	110%	

Maximum EGT:	°C	°F
Starting (10 seconds)	974	1785
Running	731	1348

CL-601 3A & 3R Variants

Airspeed Limits (CAS)

V_{mo} and M_{mo} (maximum operating)		m.p.h.	Knots	Mach
Sea level to 10000 ft.		345	300	-
10000 ft. to 21330 ft.		420	365	-
21330 ft. to 25640 ft.		-	-	0.79
25640 ft. to 28720 ft.		385	335	
above 28720 ft.		-	-	0.835
V_{fe} (Flaps extended)	20°	265	230	
	30°	226	196	
	45°	215	187	
V_a (maneuvering) (See Flight Manual for variation of V_a with altitude and aircraft weight).				
V_{1o} (Landing gear operation)		226	196	
V_{1e} (Landing gear extended)		288	250	

C.G. Range (See NOTE 1)

Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
25000 to 42250	16% (+502.848)	- - -
43250	- - -	30% (+515.818)
31000	- - -	35% (+520.450)
25000	- - -	35% (+520.450)

Straight line variation between points given.

Datum: Fuselage station 0, located 375 inches forward of weighing datum jig point.

Mean Aerodynamic Chord (MAC): 92.644 in. (Leading edge of MAC from datum at +488.025 in.)

Leveling Means: Target plate and plumb bob bracket within rear fuselage, at fuselage station 718.

Maximum Weights (See NOTE 1)

	lb. *
Ramp	43250
Takeoff	43100
Landing	36000
Zero Fuel	29500
Minimum flight weight	25000

*Certain aircraft are eligible for operation at different weights. See AFM as in approved publications. 601-3R Variant for aircraft S/N 5135 and subsequent.

Minimum Crew: Two (Pilot and Co-pilot)

Maximum Occupants: Twenty-two (includes crew).

CL-604 Variant

Engine Limits	CF34-3B	SL Static Thrust (lb.)	Compressor RPM		Interturbine Temp.		
			LP %N1	HP %N2	°C	°F	Time Limit
	Max. takeoff (APR operating)	9220	98.6	99.4	900	1650	5 minutes
	Max. takeoff (APR not operating)	8729	96.2	98.2	884	1623	5 minutes
	Max. continuous	9140	98.6	99.2	874	1605	
	Idle range			62.9-64.0			
	Min. Idle in icing conditions			64.0			
	Transient:						
	Takeoff (APR operating)				928	1702	2 minutes
	Takeoff (APR not operating)				900	1650	2 minutes
	Start/relight				899	1650	25 seconds
					885	1625	50 seconds

NOTE

1. Above 40000 feet, engine anti-ice bleed or air conditioning unit must be selected ON for each engine.

2. Engine Limits with APR Operating are only applicable to Outside Air Temperatures of -4°F (-20°C) and above.

		°C	°F
Oil Temperature	Maximum Permissible (15 minutes Maximum):	+163	325
	Maximum for Single Engine Climb (60 minutes maximum)	+155	311
	Maximum continuous:	+150	302
	Minimum for starting:	- 40	- 40
Oil Pressure	Maximum Transient Cold Start:	115 psi (10 min. maximum)	
	Maximum Continuous:	95 psi	
	Minimum at steady state idle:	25 psi	
	at takeoff (power):	45 psi	
APU Limits	Maximum RPM 110%		
	Maximum EGT:	°C	°F
	Starting (10 seconds)	974	1785
	Running	731	1348

CL-604 Variant

Airspeed Limits (CAS)	V_{mo} and M_{mo} (maximum operating)		m.p.h.	Knots	Mach
	Sea level to 8000 ft.		345	300	-
	8000 ft. to 22160 ft.		400	348	-
	22160 ft. to 26570 ft.		-	-	0.78
	26570 ft. to 30997 ft.		366	318	
	above 30997 ft		-	-	0.85
	V_{fe} (Flaps extended)	20°	266	231	
		30°	227	197	
		45°	217	189	
	V_a (maneuvering) (See Flight Manual for variation of V_a with altitude and aircraft weight).				
	V_{1o} (Landing gear operation)		227	197	
	V_{1e} (Landing gear extended)		288	250	

C.G. Range (See NOTE 1)

Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
26000 to 38000	20% (+506.553)	- - -
39500 to 44750	16%(+502.847)	- - -
47700	20% (+506.553)	- - -
47700 to 43000	- - -	38% (+523.228)
38000 to 26000	- - -	35% (+520.449)

Straight line variation between points given.

Datum: Fuselage station 0, located 375 inches forward of weighing datum jig point.

Mean Aerodynamic Chord (MAC): 92.644 in. (Leading edge of MAC from datum at +488.025 in.)

Leveling Means: Target plate and plumb bob bracket within rear fuselage, at fuselage station 718.

Maximum Weights (See NOTE 1)

	lb. *
Ramp	47700
Takeoff	47600
Landing	38000
Zero Fuel	32000
Minimum	26000

*Certain aircraft are eligible for operation at different weights. See AFM as in approved publications. 601-3R Variant for aircraft S/N 5135 and subsequent.

Minimum Crew: Two (Pilot and Co-pilot)

Maximum Occupants: Twenty-two (includes crew).

3A variant
Fuel Capacity

	U.S. Gal	Imp. Gal.	Kg.	Weight, lb.	Mom.Arm-in.
Usable					
2 main tanks (each)	722	601	2227	4909	(+506.6)
Fuselage tanks	1010	841	3115	6868	(+455.6)
Total	2454	2043	7569	16686	

See NOTE 1(b) for system fuel.

3R variant
Fuel Capacity

	U.S. Gal	Imp. Gal.	Kg.	Weight, lb.	Mom.Arm-in.
Usable					
2 main tanks (each)	722	601	2227	4909	(+506.6)
Fuselage tanks	1010	841	3115	6868	(+455.6)
Tailtank	187.7	156.24	579	1276	(+816.7)
Total	2641.7	2199.24	8148	17962	

See NOTE 1(b) for system fuel.

604 variant
Fuel Capacity

	U.S. Gal	Imp. Gal.	Kg.	Weight, lb.	Mom.Arm-in.
Usable					
2 main tanks (each)	722	601	2227	4909	(+506.6)
Fuselage tanks	1062	885	3275	7222	(+450.6)
Tailtank	466	387.9	1437	3169	(+771.7)
Total	2972	2474.9	9166	20209	

See NOTE 1(b) for system fuel.

Oil Capacity

601-3A Variant*	U.S. Gal.	Imp. Gal.	Kg.	Weight, lb.	Mom.Arm-in.
2-engines (each)	1.70	1.42	5.94	13.09	(+653.0)
Total	3.40	2.83	11.88	26.18	(+653.0)
Usable					
2-engines (each)	1.38	1.14	4.80	10.59	(+653.0)
Total	2.75	2.29	9.60	21.18	(+653.0)
See NOTE 1(c) for system oil.					
APU					
usable	.408	.340	1.43	3.144	(+646.0)
Total	.714	.594	2.49	5.5	(+646.0)
unusable	.306	.254	1.06	2.356	(+646.0)

*601-3R Variant & 604 Variant - same as 601-3A, except as listed in the AFM approved publication.

Maximum Operating Altitude

Take off and landing: 10000 ft.
En route: 41000 ft.

Control Surface Movements

Rudder	25°(+ 1°, -0.5°)Left	25°(+ 1° or -0.5°) Right
Elevator	23.6°(+ or -1.0°) Up	18.4°(+ or -1.0°) Down
Horizontal stabilizer	0°(+0.5° or -0.25°)LE Up	-9°(+ or - 0.5°) LE Down
Aileron	20.8°(+ or - 1°)Up	21.3°(+ or - 1°) Down
Flap - Inboard		0° -45°(+ or - 1°) Down
- Outboard		0° -46.7°(+ or -1°) Down
Flight spoiler	0° -40°(+3°, -0°) Up	

Serial Numbers Eligible

5001 and subsequent

Service Information:

Service Bulletins, structural repair manuals, and aircraft flight manuals which contain a statement that the document is Transport Canada approved or Transport Canada approved through the Manufacturers Design Approval Representative are accepted by the FAA and are considered FAA approved. These approvals pertain to the type design only.

IV - Model CL-600-2B19 (Transport Category), Approved January 21, 1993, by the FAA and July 31, 1992, by Transport Canada.

Engines

Two General Electric CF-34-3A1 or
Two General Electric CF-34-3B1

Engines may be intermixed in accordance with AFM as listed in Approved Publications.

Type	Specifications			
	Canada	U.S.A.	U.K.	Romanian
Jet A	CAN2-3.23	ASTM D1655	D. Eng RD2494	
Jet A-1	CAN2-3.23	ASTM D1655	D. Eng RD2494	STAS 5639/88 TH†
Grade JP-5		MIL-T-5624	D. Eng RD2452	
Grade JP-8	-	MIL-T-83133A	D. Eng RD2453	
Jet B	CAN2-3.22	ASTM D1655	D. Eng RD2486	
JP-4	CAN2-3.22	MIL-T-5624	D. Eng RD2486	

†Fuel Additives Restricted to those listed in AFM (CSP-A-012) (Limitations, Fuel Additives) and/or antistatic STADIS-450 (max. 3ppm).

Oil

Engine, APU and IDG:
MIL-L-7808 (Type I) or MIL-L-23699 (Type II) or CASTROL 4000. *
* Mixing of different types of oils is prohibited.

Engine Limits Conditions

	Fan RPM N_1%	Core RPM N_2%	ITT °C	ITT °F	Time Limit (Min)
Max. Take - off (APR Operating)	98.6	99.4	900	1650	5***
			928	1702	2*
Normal Take-off	96.2	98.2	884	1623	5***
			900	1650	2*
Max. Continuous	98.6	99.2	860 (874) (3A1/3B1)	1580/1605 (3A1/3B1)	
Idle Range	-	56.5 to 68.0**	-	-	-
Acceleration	-	-	900	1652	-
Starting	-	20.0	900	1652	-

* 2 minutes out of 5 total transient.

** Refer to Idle Speed Limit Chart in the AFM

If N_2 idle RPM is more than 2% lower, do not advance thrust lever above 70% N_2 until N_2 idle RPM has stabilized to within normal limits.

*** Transient limits.NOTE:

Above 40000 feet, one air conditioning unit or cowl anti-ice must be selected on for each engine.

		°C	°F
Oil Temperature	Maximum Permissible (15 minutes Maximum):	+163	325
	Maximum Continuous	+155	311
	Minimum for Starting	-40	-40

Oil Pressure	Maximum Transient (after cold start)	156 psi (130 psi at idle, 10 minutes maximum)*
	Maximum Continuous	115 psi maximum
	Take-off Power	45 psi minimum
	Steady State Idle	25 psi minimum

* Engine must remain at idle until oil pressure returns to normal range.

APU GARRETT GTCP-36-150RJ

APU Limits Maximum RPM: 107%

Maximum EGT:	°C	°F
Starting	974	1785*
Running	743	1369

* Not to be exceeded under any operating condition.

Airspeed Limits			m.p.h.	knots	Mach
	V_{mo} and M_{mo} (maximum operating)				
	Sea Level to 8000 ft.		380	330	-
	8000 ft. to 25400 ft.		386	335	-
	25400 ft. to 28300 ft.		-	-	0.80
	28300 ft. to 31400 ft.		362	315	-
	31400 ft. to 41000 ft.		-	-	0.85
	V_{fe} (Flaps Extended)	8°	265	230	-
		20°	265	230	-
		30°	226	196	-
		45°	220	191	-
	V_a (maneuvering)				
	(See Flight Manual for variation of V_a with altitude and aircraft weight).				
	V_{LO} (Landing Gear Operation)		288	250	*-
			230	200	**-
	V_{LE} (Landing Gear Extended)		288	250	-

* extending , ** retracting

C.G. Range:-

Max T/O 47 450 lb			Max T/O 51 000 lb		
Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)	Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (STA)
25480	16.5% (+510.201)	-	25480	16.5% (+510.201)	-
30000 to 34000	11.0% (504.732)	-	30000 to 34000	11.0% (+504.732)	-
36000 to 47700	9.0 % (+502.744)	-	36000 to 51250	9.0% (+502.744)	-
47700	-	-	51250	-	24% (+517.659)
47700 to 36000	-	35% (528.596)	50000 to 36000	-	35% (+528.596)
34000 to 30000	-	32% (+525.613)	34000 to 30000	-	32% (+525.613)
25480	-	27% (+520.642)	25480	-	27% (+520.642)

NOTES: 1) Effect of landing gear retraction on CG position is negligible.
2) Straight line variation between points given.

C. G. Range:- Max T/O 53 000 lb

Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
25480	16.5% (+510.201)	-
30000 to 34000	11.0% (504.732)	-
36000 to 53250	9.0 % (+502.744)	-
53250	24.0 %	-
53250 to 36000	-	35% (528.596)
34000 to 30000	-	32% (+525.613)
25480	-	27% (+520.642)

NOTES: 1) Effect of landing gear retraction on CG position is negligible.
2) Straight line variation between points given.

Datum Fuselage station 0, located 375 inches forward of weighing datum jig point.

Mean Aerodynamic Chord (MAC) 99.43 inches (MAC leading edge at fuselage sta. 494.793)

Leveling Means Target plate and plumb bob bracket within rear fuselage, at fuselage station 718.75.

Maximum Weights

	lb.	lb.	lb.	lb.	lb.	lb.
Ramp	47700	51250	51250	53250	53250	53250
Takeoff	47450	51000	51000	53000	53000	53000
Landing	44700	46750	47000	46750	47000	47000
Zero Fuel	42200	44000	44000	44000	44000	39500
Minimum flight weight	30000	30000	30000	30000	30000	30000

NOTE: The maximum take-off weight and/or maximum landing weight may be further limited due to performance considerations (refer to Airplane Flight Manual).

Minimum Crew Two (Pilot and Co-pilot)

Maximum Occupants Fifty-five (50 pax, 4 crew, and 1 flight observer)

CL-600-2B19 Green Aircraft Configuration
Refer to Note 5.

	Load *		Weight *	
Fuel Capacity (usable)	U.S. Gal.	Imp. Gal.	Kg.	lb.
2 main tanks (each)	700.0	582.8	2159	4760
Center Tank	735.0	612.0	2267	4998
Total	2135.0	1669.6	6585	14518

* Pressure refueling (based on 0.8028 kg/L)

Oil Capacity	Load		Weight	
	U.S. Gal.	Imp. Gal.	kg.	lb.
2 Engines (each)	1.70	1.42	5.94	13.09
Total	3.40	2.84	11.88	26.18
Usable				
2 Engines (each)	1.38	1.14	4.80	10.59
Total	2.76	2.29	9.60	21.18

Maximum Operating Altitude	Take off and landing:	10000 ft.
	En route:	41000 ft.

Control Surface Movements			
	Rudder	33° Left	33° Right
	Horizontal Stabilizer	2° LE Up	-13° LE Down
	Aileron	25° Up	21.3° Down
	Elevator	23.6° Up	18.4° Down
	Flight Spoiler	50° Up	
	Ground Spoiler	45° Up	
	Spoileron	50° Up	
	Flap - Inboard		45.09° Down
	- Outboard		41.58° Down

Serial Numbers Eligible: 7001 and subsequent

Service Information: Service Bulletins, structural repair manuals, and aircraft flight manuals which contain a statement that the document is Transport Canada approved or Transport Canada approved through the Manufacturers Design Approval Representative are accepted by the FAA and are considered FAA approved. These approvals pertain to the type design only.

Data Pertinent to all Models

Approved Publications

Model CL-600-1A11

(a) Airplane Flight Manual, Canadair Publication RAG-600-101, Issue 2 (PSP 600 (U.S.) FAA, and PSP 600-1 (U.S.) for the appropriate configuration, (See NOTE 1) and approved revisions.

(b) Drawing List, Canadair Publication RAL-600-105, and later approved revisions.

Model CL-600-2A12

(a) Airplane Flight Manual, Canadair Publication PSP 601-1A, PSP 601-1A-1, PSP 601-1B and PSP 601-1B-1 for the appropriate weight configuration, (See NOTE 1) and approved revisions.

(b) Drawing List, Canadair Publication RAL-601-105, and later approved revisions.

Model CL-600-2B16

(a) Airplane Flight Manual, Canadair Publication PSP 601A-1, PSP 601A-1-1and PSP 604-1-1 for the appropriate weight configuration, (See NOTE 1) and approved revisions.

(b) Drawing List, Canadair Publication RAL-601A-105 (3A & 3R Variants) and RAL-604-0001 (604 Variant), and later approved revisions.

Model CL-600-2B19

(a) Airplane Flight Manual, Canadair Publication CSP A-012 for the appropriate weight configuration and approved revisions.

(b) Maintenance Review Board (MRB) Report and subsequent revisions as contained in the Maintenance Requirements Manual (MRM), Canadair Publication CSP A-053, Part 2 and subsequent approved revisions.

(c) Structural Repair Manual (SRM), Canadair Publication CSP A-008 and subsequent approved issues.

(d) Certification Maintenance Tasks, Canadair Regional Jet, Model CL-600-2B19 Engineering Report No. RBR-601R-167, as contained in Part 2 to the Maintenance Requirements Manual (MRM), Canadair Publication CSP A-053, and subsequent approved revisions.

Import Eligibility

A U.S. Airworthiness Certificate may be issued on the basis of the Canadian Department of Transport "Certificate of Airworthiness for Export" signed by the Minister of Transport. This form must contain the following statement:

a) Model CL-600-1A11
"This certificates that the aircraft described below has been manufactured in conformity with data forming the basis for the DOT Aircraft Type Approval No. A-131, as modified by Drawing List, Canadair Publication RAL-600-105, and later approved revisions (FAA Type Certificate No. A21EA)".

b) Model CL-600-2A12
"This certifies that the aircraft described below has been manufactured in conformity with data forming the basis for the DOT Aircraft Type Approval No. A-131 as modified by Drawing List, Canadair Publication RAL-601-105, and later approved revisions (FAA Type Certificate No. A21EA)".

c) Model CL-600-2B16 (3A & 3R Variants)
"This certifies that the aircraft described below has been manufactured in conformity with data forming the basis for the DOT Aircraft Type Approval No. A-131 as modified by Drawing List, Canadair Publication RAL-601A-105 and later approved revisions (FAA Type Certificate No. A21EA)".

Model CL-600-2B16 (604 Variant)
"This certifies that the aircraft described below has been manufactured in conformity with data forming the basis for the DOT Aircraft Type Approval No. A-131 as modified by Drawing List, Canadair Publication RAL-604-0001 and later approved revisions (FAA Type Certificate No. A21EA)".

d) Model CL-600-2B19
"This certifies that the aircraft described below has been manufactured in conformity with data forming the basis for the Transport Canada Type Approval No. A-131 and includes the minimum type design defined in document RAZ-601R-111 as being required to comply with the basis for the FAA Type Certificate No. A21EA".

The approved type design appropriate to the "as delivered" configuration of a particular CL-600-2B19 airplane is defined in the document RAL-601R-XXXX. (XXXX represents the Serial Number for the airplane concerned).

Model CL-600-2B19 Green Configuration
For CL-600-2B19 Green Configuration and associated modifications refer to NOTE 4.

Certification Basis

Model CL-600-1A11, CL-600-2A12, and CL-600-2B16 (3A & 3R Variants)
FAR Part 25 dated February 1, 1965, including Amendments 25-1 through 25-37, plus FARs 25.675(a), 25.685(a), 25.733(c), 25.775(e), 25.787(c), 25.815, 25.841(b), 25.951(a), 25.979(d) and (e), 25.1041, 25.1143(e), 25.1303(a), 25.1322, 25.1385(c), 25.1557(b), 25.1583(a), of Amendment 25-38; FARs 25.901(b) and (c), 25.903(c) and (e), 25.933(a), 25.943, 25.959, 25.1091(a) and (d), 25.1145(c), 25.1199(b) and (c), 25.1207, 25.1549, 25.1585(a)(9) of Amendment 25-40; and FAR 25.1309 of Amendment 25-41; FAR 25.1353(c) of Amendment 25-42; FAR's 25.571 and 25.629(d)(4) (v) of Amendment 25-45; FARs 25.351 and 25.603 of Amendment 25-46.

Model CL-600-2B16 (604 Variant)
FAR Part 25 dated February 1, 1965, including Amendments 25-1 through 25-78 with the following exceptions: FAR Part 25 at Amendment 25-37 for paragraphs: 109, 149, 365, 561, 625, 701, 772, 783 (except 783(f)), 785 (except 785(g)), 789, 791, 801, 803, 807, 809, 811, 812, 813, 831, 853, 855, 857, 1307, 1359, 1415, & 1419; FAR Part 25 at Amendment 25-37 for existing installations and Amendment 25-78 for new installations for paragraphs: 963, 965, 994, 997, and 1438; FAR Part 25 at Amendment 25-38 for paragraphs 787 and 1439; FAR Part 25 at Amendment 25-40 for paragraph 25.973; FAR Part 25 at Amendment 25-37 for paragraph 25.109 (see note 7); FAR Part 25 at Amendment 25-44 for paragraph 25.1413; FAR Part 25 at Amendment 25-54 for paragraph 851; FAR Part 25 at Amendment 25-80 for paragraph 1316. New FAR Part 25 requirements 562, 810, 819, 832, 858, 869, (a) & (b), 1421, 1423 and 1450 are not part of the certification basis.

Model CL-600-2B19
FAR Part 25 dated February 1, 1965, including Amendments 25-1 through 25-62 with the following exceptions; FAR 25.109 at Amendment 25-41, FAR 25.832 not included, FAR 25.1401 at Amendment 25-40, FAR 25.1438 not included and FAR 25.783(f) at Amendment 25-23 for the cargo compartment door, the main avionics compartment door and the service/emergency door. FAR 25.773(b)(2) and 25.785(h) at Amendment 25-72.

Additional FAA Requirement

(a) Model CL-600-1A11
(1) FAR Part 36 dated December 1, 1969, as amended through Amendment 36-9 inclusive.
(2) SFAR 27 dated February 1, 1974, as amended through Amendment SFAR 27-2.
(3) Special Conditions No. 25-94-EA-12 dated March 26, 1980, (FAA Docket No. 16921) and Amendment No. 1 dated September 11, 1981.

Date of application for Type Certificate August 3, 1976. Type Certificate A21EA issued November 7, 1980.

(b) Model CL-600-2A12
(1) FAR Part 36 dated December 1, 1969, as amended through Amendments 36-9 inclusive.
(2) SFAR 27 dated February 1, 1974, as amended through Amendment SFAR 27-2.
(3) Special Conditions No. 25-ANM-1 dated March 8, 1983.
Date of application for amendment to Type Certificate May 1, 1981. Type Certificate A21EA amended March 11, 1983.

(c) Model CL-600-2B16 (3A & 3R Variants)
(1) FAR Part 36 dated December 1, 1969, as amended through Amendments 36-9 inclusive.
(2) SFAR 27 dated February 1, 1974, as amended through Amendment SFAR 27-2.
(3) Special Conditions No. 25-ANM-1 dated March 8, 1983.

Date of application for amendment to Type Certificate March 3, 1986.
Type Certificate A21EA amended April 30, 1987.

(d) Model CL-600-2B16 (604 Variant)
(1) FAR Part 36 dated December 1, 1969, as amended through Amendments 36-20 inclusive.
(2) FAR Part 34 dated August 25, 1990 as amended through Amendment 34-1.
(3) Special Conditions No. 25-ANM-109 dated October 31, 1995 (HIRF).

Date of application for Change to Type Design June 14, 1993.
Change to Type Design approved November 2, 1995.

(e) Model CL-600-2B19

(1) FAR Part 36 dated December 1, 1969, as amended through Amendments 36-18 inclusive.
(2) Applicable portions of FAR 34 (previously codified as SFAR 27).
(3) Special Conditions No. 25-ANM-61 dated July 22, 1992.

Date of application for amendment to Type Certificate May 26, 1988.
Type Certificate A21EA amended January 21, 1993.

Equivalent safety has been established for the following requirements:
(CL-600-1A11, CL-600-2A12, and CL-600-2B16).
(1) FAR 25.773(b)(2) DV Window
(2) 25.955(a)(4) Blocked Flow Meter Fuel Flow Requirements
(3) FAR 25.201 Stall Determination

Equivalent safety has been established on the CL-600-2B16 (604 Variant) for the following requirements:
(1) FAR 25.955 (a)(4) Blocked Flow Meter Fuel Flow Requirements
(2) Several FAR's for the use of Reduced Minimum Operating Speed Factors

Equivalent safety has been established on the CL-600-2B19 for the following requirements:
(1) FAR 25.811(d)(2) Emergency Exit Marking Sign
(2) FAR 25.813(c)(1) Access to Type III exit-seat cushion intrusion
(3) Several FAR's for the use of 1-g Stall Speed (nonstructural items)

Compliance with the following optional requirements has been established: (CL-600-1A11, CL-600-2A12, and CL-600-2B16):
(1) Ditching provisions of FAR 25.801
(2) Ice Protection of FAR 25.1419

Compliance with the following optional requirements has been established for the CL-600-2B16 (604 Variant):
(1) Ditching provisions of FAR 25.801
(2) Ice Protection of FAR 25.1419

Compliance with the following optional requirements has been established for the CL-600-2B19:
(1) Ice Protection of FAR 25.1419
(2) Ditching provisions of FAR 25.801 when the safety equipment requirements of FAR 25.1411 and the ditching equipment requirements of FAR 25.1415 are satisfied.

Equipment

The basic equipment as prescribed in the applicable airworthiness requirements (See Certification Basis) must be installed in the aircraft for certification.

NOTE 1

This Aircraft Type Certificate Data Sheet defines a configuration which does not include passenger provision for the CL-600-1A11, CL-600-2A12, and CL-600-2B16 models. Carriage of persons in the cabin is permitted when an approved seating arrangement and related required passenger provisions are incorporated.

(a) Current weight and balance report including the list of equipment included in the certificated empty weight, and loading instructions when necessary, must be provided for each aircraft at the time of original certification.

(b) Model CL-600-1A11, CL-600-2A12, and CL-600-2B16
System fuel, which must be included in the empty weight, is the amount of fuel required to fill the system plumbing and tanks to the undrainable level plus unusable fuel in the fuel tanks. The total amount of "system fuel" is 16.0 gal. total, 109 lb., (+500.00).

Model CL-600-2B19
System fuel, which must be included in the empty weight, is the amount of fuel required to fill the system plumbing and tank to the undrainable level plus unusable fuel in the fuel tanks. The total amount of "system fuel" is 14.5 U.S. Gal., 97 lb. (+494.3).

(c) Model CL-600-1A11
System oil, which must be included in the empty weight, is the amount of oil necessary for engine lubrication. The total amount of "system oil" is as follows:

7.38 U.S. gal. (total) 56.8 lb., (+623)

Model CL-600-2A12 and CL-600-2B16
System oil, which must be included in the empty weight, is the amount of oil necessary for engine lubrication. The total amount of "system oil" is as follows:

6.1 U.S. gal. (total) 47 lb., (+680.5)

Model CL-600-2B19
System oil, which must be included in the empty weight, is the amount of oil necessary for engine lubrication. The total amount of "system oil" is as follows:

5.83 U.S. gal. (total) 47 lb., (+785.67)

(d) Model CL-600-1A11
Aircraft which incorporate Canadair Limited Modification Summaries:
1) 600-556 Modified main landing gear wheel,
2) 600-592 Modified main landing gear sidestay,
3) 600-1933 Revised airspeed limitation placard.

may be operated to the following limitations (eligible Serial Numbers 1002, 1004 through 1037):

Maximum Weight	lb.
Ramp	38650
Takeoff	38500
Landing	32500
Zero Fuel	28500

Maximum Occupants Twenty-two (includes crew)

C.G. Range Weight, lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 38650	16 % (+502.848)	- - -
38650	- - -	28% (+513.965)
25800	- - -	33% (+518.598)
24000	- - -	33% (+518.598)

Straight line variation between points given.

Maximum Operating Altitude		
Takeoff and landing	10000 ft.	
En route	40000 ft.	
	41000 ft.	with Canadair Limited Modification Summaries 600-1923 & 600-8330 incorporated.

Model CL-600-1A11

(e) Aircraft which incorporate Canadair Limited Modification Summaries:

1) 600-594 Landing gear for 40400 lb. takeoff weight aircraft,
2) 600-616 Wheels and brakes for the 40400 lb. takeoff weight aircraft,
3) 600-643 Structural reinforcement at wing B.L. O rib,
4) 600-752 Modified anti-skid unit,
5) 600-817 Stall protection system computer for the 40400 lb. takeoff weight aircraft,
6) 600-8150 Placard for the 40400 lb. takeoff weight aircraft,
7) 600-760 Drop down passenger door-production improvement (required only on S/N 1024 & subsequent).

may be operated to the following limitations (eligible Serial Numbers 1002, 1004 and subsequent):

Maximum Weight	lb.
Ramp	40550
Takeoff	40400
Landing	36000
Zero fuel	28500

Maximum Occupants Twenty-two (includes crew)

C.G. Range (Aircraft without Canadair Modification Summary 600-8265)

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 40550	16 % (+502.848)	-
40550	-	27% (+513.039)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
27500	-	33% (+518.598)
24000	-	33% (+518.598)

Straight line variation between points given.

C.G. Range (Aircraft with Canadair Modification Summary 600-8265 Incorp)

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 40550	16 % (+502.848)	-
40550	-	27% (+513.039)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
28500	-	35% (+520.450)
24000	-	33% (+520.450)

Straight line variation between points given.

Maximum Operating Altitude		
Takeoff and landing	10000 ft.	
En route	40000 ft.	
	41000 ft.	with Canadair Modification Summaries 600-1923 & 600-8330 incorporated

Model CL-600-1A11

(f) Airspeed Limits (CAS)

Aircraft which, in addition to the Canadair Modification Summaries essential for operation at a maximum takeoff weight of 40400 lb., also incorporate the following Canadair Modification Summary:

1) 600-665 Revised Vmo/Mmo outputs of ADC and limitations placard may be operated at the following limitations:

Vmo and Mmo (maximum operating)	m.p.h.	Knots	Mach.
Sea level to 10000 feet	345	300	-
Above 10000 feet	420	365	0.835

Extension of the flight spoilers at airspeeds above Mach = 0.79 is not permitted unless the following additional Canadair Modification Summaries are incorporated:

1) 600-512 Prevention of spoiler asymmetry
2) 600-809 Dormant failure protection of the flight spoiler detent
3) 600-8212 Hydraulic pipe routing to suit spoiler detent mechanism.

Model CL-600-1A11

(g) Aircraft Serial Numbers 1086 and subsequent and aircraft incorporated the following:

1) Either
   a) Canadair Service Bulletin
      600-0378 - Modification - Stall Protection System - Stall Strip Removal and Altitude Compensation

or b) Supplementary Type Certificate SA99NE - Wing Stall Strip Removed.

and

2) Canadair Service Bulletin
   600-0379 - Modification - Tires and Airspeed Limitation Placards - 41100 Pounds Takeoff Weight.

may be operated to the following limitations (eligible Serial Numbers 1002, 1004 and subsequent)

Maximum Weight	lb.
Ramp	41250
Takeoff	41100
Landing	36000
Zero fuel	28500

Maximum Occupants Twenty-two (includes crew).

C.G. Range Aircraft 1004, 1009, 1053 to 1056, 1066 and subsequent and Aircraft incorporating Canadair Service Bulletin 600-0221

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 41250	16% (+502.848)	-
41250	-	26% (+512.112)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
28500	-	35% (+520.450)
24000	-	35% (+520.450)

Straight line variation between points given.

C.G. Range (Other Aircraft)

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 41250	16% (+502.848)	-
41250	-	26% (+512.112)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
27500	-	33% (+518.598)
24000	-	33% (+518.598)

Straight line variation between points given.

Maximum Operating Altitude	
Takeoff and landing	10000 ft.
En route	41000 ft.

Airspeed Limits (CAS)

Vmo and Mmo (maximum operating)	m.p.h.	Knots	Mach.
Sea level to 10000 feet	345	300	-
Above 10000 feet	420	365	0.835

Extension of the flight spoilers at airspeeds above Mach = 0.80 is not permitted on Aircraft S/N 1005 to 1008, 1010 to 1052, 1057 to 1066 not incorporating Canadair Service Bulletin 600-0086 Modification - Spoilers - Ground Spoiler Activation and Flight Spoiler Detent Mechanism.

Model CL-600-1A11

(h) Aircraft incorporating the following Canadair Service Bulletins
   a) 600-0350 Modification - Engine Speed Indicating- N_1 Fan Speed Indicator
   b) 600-0379 Modification - Tires and Airspeed Limitation Placards - 41100 lb. Takeoff Weight.
   c) 600-0401 Modification - Winglets - Addition

With Aircraft Serial Numbers 1005 to 1008 and 1010 to 1051 incorporating the following additional Canadair Service Bulletins

either 600-0096 Modification - Nose Landing Gear Steering
or 600-0380 Modification - Nose Gear - Steer by Wire.

may be operated to the following limitations (eligible Serial Numbers 1002, 1004 and subsequent).

Maximum Weight	lb.
Ramp	41250
Takeoff	41100
Landing	36000
Zero Fuel	28500

MaximumOccupants Twenty-two (includes crew).

C.G. Range Aircraft 1004, 1009, 1053 to 1056, 1066 and Subsequent and Aircraft Incorporating Canadair Service Bulletin 600-0221

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 41250	16% (+502.848)	-
41250	-	26% (+512.112)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
28500	-	35% (+520.450)
24000	-	35% (+520.450)

Straight line variation between points given.

C.G. Range (Other Aircraft)

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 41250	16% (+502.848)	-
41250	-	26% (+512.112)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
27500	-	33% (+518.598)
24000	-	33% (+518.598)

Straight line variation between points given.

Maximum Operating Altitude	
Takeoff and landing	10000 ft.
En route	41000 ft.

Airspeed Limits (CAS)		m.p.h.	Knots	Mach.
Vmo and Mmo (maximum operating)				
Sea level to 10000 feet		345	300	-
10000 ft. to 21420 ft.		420	365	-
21420 ft. to 25740 ft.		-	-	0.79
25740 ft. to 28640 ft.		385	335	-
above 28640 ft.		-	-	0.835
Vfe (Flaps extended)				
	20°	265	230	
	30°	226	196	
	45°	215	187	

Extension of the flight spoilers at airspeeds above Mach = 0.79 is not permitted on Aircraft S/N 1005 to 1008, 1010 to 1052, 1057 to 1066 not incorporating Canadair Service Bulletin 600-0086 Modification - Spoilers - Ground Spoiler Activation and Flight Spoiler Detent Mechanism.

Model CL-600-1A11

(i) Aircraft incorporating the following Canadair Service Bulletins

a) 600-0350 Modification - Engine Speed Indicating- N_1 Fan Speed Indicator

b) 600-0446 Modification - Placard-41250 lb. Take-off Weight (Aircraft with Winglets).

c) 600-0401 Modification - Winglets - Addition

With Aircraft Serial Numbers 1005 to 1008 and 1010 to 1051 incorporating the following additional Canadair Service Bulletins

either 600-0096 Modification - Nose Landing Gear Steering

or 600-0380 Modification - Nose Gear - Steer by Wire.

may be operated to the following limitations (eligible Serial Numbers 1002, 1004 and subsequent).

Maximum Weight	lb.
Ramp	41400
Takeoff	41250
Landing	36000
Zero Fuel	28500

Maximum Occupants	Twenty-two (includes crew).

C.G. Range Aircraft 1004, 1009, 1053 to 1056, 1066 and Subsequent and Aircraft Incorporating Canadair Service Bulletin 600-0221

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
24000 to 41400	16% (+502.848)	-
41400	-	26% (+512.112)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
28500	-	35% (+520.450)
24000	-	35% (+520.450)

Straight line variation between points given.

C.G. Range (Other Aircraft)

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
		-
24000 to 41400	16% (+502.848)	-
41400	-	26% (+512.112)
38000	-	31% (+516.745)
31000	-	31% (+516.745)
27500	-	33% (+518.598)
24000	-	33% (+518.598)

Straight line variation between points given.

Maximum Operating Altitude

Takeoff and landing	10000 ft.
En route	41000 ft.

Airspeed Limits (CAS)	m.p.h.	Knots	Mach.
Vmo and Mmo (maximum operating)			
Sea level to 10000 feet	345	300	-
10000 ft. to 21420 ft.	420	365	-
21420 ft. to 25740 ft.	-	-	0.79
25740 ft. to 28640 ft.	385	335	-
above 28640 ft.	-	-	0.835

Vfe (Flaps extended)

20°	265	230
30°	226	196
45°	215	187

Extension of the flight spoilers at airspeeds above Mach = 0.79 is not permitted on Aircraft S/N 1005 to 1008, 1010 to 1052, 1057 to 1066 not incorporating Canadair Service Bulletin 600-0086 Modification - Spoilers - Ground Spoiler Activation and Flight Spoiler Detent Mechanism.

Model CL-600-2A12

(j) Aircraft Serial Numbers 3018 and subsequent and aircraft incorporating the following Canadair Service Bulletin 601-0032 - Modification - Tires and Airspeed Limitation Placards 43100 lb. Takeoff Weight may be operated to the following limitations (eligible Serial Numbers 1003, 3001 and subsequent)

Maximum Weight	lb.
Ramp	43250
Takeoff	43100

Maximum Occupants Twenty-two (includes crew).

C.G. Range

Weight lb.	Forward Limit % MAC (Sta.)	Aft Limit % MAC (Sta.)
25000 to 43250	16% (+502.848)	- - -
43250		30% (+515.818)
31000	- - -	35% (+520.450)
25000	- - -	35% (+520.450)

Straight line variation between points given.

NOTE: 2

Model CL-600-1A11

All placards must be installed in accordance with Canadair Limited Drawings: 600-40402, 600-40452, 600-51000, 600-51002, 600-51004

Model CL-600-2A12

All placards must be installed in accordance with Canadair Limited Drawings: 601-40402, 601-40452, 600-51000, 600-51002, 601-51004.

Model CL-600-2B16
All placards must be installed in accordance with Canadair Limited Drawings: 601-40402, 601-40452, 601A51000, 601A51002, 601A51004.(3A & 3R Variants)
601-40402, 601-40452 & 604-51000 (604 Variant)

Model CL-600-2B19
All placards must be installed in accordance with Canadair Limited Drawings: 601R47600, 601R47602, 601R47700.
Note: Customized markings and placards drawings are not included.

NOTE: 3

Model CL-600-1A11
The airplane life limits and repetitive inspections for components and equipment are listed in Canadair Time Limits/Maintenance Checks, PSP 605. These limitations may not be changed without FAA Engineering approval. This document with Canadair Maintenance Manual, PSP 602 and Job Inspection Card Manual PSP 622, NDT-612 contain all information essential for proper maintenance.

Model CL-600-2A12
The airplane life limits and repetitive inspections for components and equipment are listed in Canadair Time Limits/Maintenance Checks, PSP 601-5. These limitations may not be changed without FAA Engineering approval. This document with Canadair Maintenance Manual, PSP 601-2 and Job Inspection Card Manual PSP 601-22, NDT-612 contain all information essential for proper maintenance.

Model CL-600-2B16
The airplane life limits and repetitive inspections for components and equipment are listed in Canadair Time Limits/Maintenance Checks, PSP 601A-5 (3A & 3R Variants) and PSP 604-5 (604 Variant). These limitations may not be changed without FAA Engineering approval. This document and Canadair Maintenance Manual, PSP 601-2 (3A & 3R Variants) and PSP 604-2 (604 Variant), and/or Job Inspection Card Manuals PSP601A-22 (3A) and/or PSP 601R-22 (3R), PSP604-22 (CL604), NDT604-12 contain all information essential for proper maintenance.

Model CL-600-2B19
The airplane life limits and repetitive inspections for components and equipment and information essential for proper maintenance, are listed in Canadair Program Document CSP A-053, Part 2. These limitations may not be changed without FAA Engineering approval.

NOTE 4:

Model CL-600-2B19
Major modifications which define the aircraft as the “Green Configuration” are recorded in document RAZ-601R-110 (Definition of RJ type design for Transport Canada approval), as Appendix 2 to that document.

NOTE 5 :

Model CL-600-2B19
The green aircraft type design does not include passenger provisions. Carriage of persons in the cabin is permitted when an approved seating arrangement and related required passenger provisions are incorporated in accordance with the Type Approval Basis.
Aircraft delivered in the “Green Configuration” and incorporating Mod. Summary TC60255 (Blocking of Emergency Exits) are limited to carrying a maximum of twenty-two (22) occupants including the crew and no more than 19 passengers in accordance with FAR 25 requirements.

NOTE 6

Model CL-600-2B19
For all weather flight capability the Regional Jet aircraft is certified to operate in CAT II conditions, except when the aircraft is installed with the HGS system (TC 601R60262), in which case the aircraft is certified to operate in CAT IIIa conditions.

NOTE 7 Model Cl-600-2B16 (CL-604 Variant)

The following additional requirements must be included with FAR 25.109 at Amendment 25-37:

1. Airplane Flight Manual information, in the form of guidance material, must be provided for supplementary operating procedures and performance information for operating on wet and contaminated runways.

2. The accelerate-stop distance and landing distance must be determined using the braking performance which is obtained with the brake conditions that are expected in service.

...END...